QUERY CONTROL FORM			RTIS USE ONLY
Application No. <u>09/937351</u>	Prepared by	CA	Tracking Number Olan, 07,7/
Examiner-GAU MaclC_2855	_ Date		Week Date 8/23/04/
	No. of queries		. 777

JACKET				
a. Serial No.	f. Foreign Priority	k. Print Claim(s)	p. PTO-1449	
b. Applicant(s)	g. Disclaimer	I. Print Fig.	q. PTOL-85b	
c. Continuing Data	h. Microfiche Appendix	m. Searched Column	r. Abstract	
d. PCT	i. Title	n. PTO-270/328	s. Sheets/Figs	
e. Domestic Priority	j. Claims Allowed	o. PTO-892	t. Other	

<u> </u>	
SPECIFICATION	MESSAGE Americant - (1+3001) 19st page
a. Page Missing	
b. Text Continuity	appears incomplete. Please Resolve.
c. Holes through Data	
d. Other Missing Text	[]
e. Illegible Text	
f. Duplicate Text	
g. Brief Description	
h. Sequence Listing	
i. Appendix	
j. Amendments	
k. Other	Thank Ya
	The state of the s
CLAIMS	
a. Claim(s) Missing	
b. Improper Dependency	
c. Duplicate Numbers	
d. Incorrect Numbering	initials CA
e. Index Disagrees	RESPONSE
f. Punctuation	
g. Amendments	
h. Bracketing	
i. Missing Text	
j. Duplicate Text	
k. Other	
	initials

Serial No. 09/771,703

Replace the paragraph on page 12 which begins "Finally in figures 5 and 6" with the following:

Finally in figures 5 and 6, respectively, the method according to the invention has been qualitatively evaluated against a reference method which is a determination of CFR by a doppler-technique. In this case however, it should be noted that the doppler-technique has its limitations and is not entirely accurate.

Please add the following paragraphs to the end of page 11:

As previously disclosed in this application, CFR can be obtained by measuring the mean transit time,  $T_{mn}$ , for a bolus dose of cold liquid by employing the response curves from lead resistance measurements and a temperature sensor respectively.

For the calculation of  $T_{mn}$ , the time constant,  $\tau$ , of an exponential function  $e^{-i\tau}$  is calculated. It has also been discovered by the inventors that  $\tau$  itself is correlated to the flow in a coronary vessel, and, therefore,  $\tau$  itself can be used to determine a valve of CFR where  $\tau_{rest}$  is the time constant of the temperature sensor response in a resting condition and  $\tau_{hyper}$  is the time constant of the temperature sensor in a hyperemic condition. Accordingly, CFR =  $\tau_{rest}/\tau_{hyper}$ .

Please delete the page of the application which contains facsimile indicia across the top which says:

"30-JAN-01 TUE 09:30 DR. LUDWIG BRANN PAT AB FAX NO. 018 568939 P. 03."

Please delete the page of the application which contains facsimile indicia across the top which says:

"30-JAN-01 TUE 09:30 DR. LUDWIG BRANN PAT AB FAX NO. 018 568939 P. 04."

Please convert the page of the application which contains facsimile indicia across the top which says: "30-JAN-01 TUE 09:30 DR. LUDWIG BRANN PAT AB FAX NO. 018